## LED Inspection Light

## Features

- Light weight & Maintenance free.
- 24 bright LED's offering a spectrum of illumination
- LED's with Long life of close to 100,000 continuous burning hours.
- IP 54 Protection
- Product made of robust, impact proof, corrosion resistance and fire retardant engineering plastic
- Low power consumption less than 3 watts
- Designed with mounting hook
- LED inspection light is devoted to offering the light with the highest quality during elevator maintenance and panel inspections.

## Technical Specifications

Rated Voltage	240V AC, 110V AC, 24V AC/DC, 12V DC		
Limit of Operating Voltage	-20% to + 10% of rated voltage		
LED	5 mm through hole LED		
Colors	White light / black handle		
Life	0.1 million hours		
LED Arrangement	Cluster		
Color Temperature	6000°K - 7000°K		
Number of LEDs	24		
Operating Temperature	-25°C to 65°C		
Storage Temperature	-30°C to 70°C		
Surge Test	2 KV		
HV Test for 60 seconds	2.5 KV		
EMI/EMC Protection	2 KV		
IP Protection	IP 54		
Power Consumption (240V)	< 3W		
Cable Type	3x 0.75 sq. mm		
Cable Length	3 meter (10 ft.)*		
Mounting	Molded plastic hook		





<sup>\*</sup> Other lengths available. Contact Altech.

## Ordering Information

Part No.	Color	Voltage	Plug**	Std. Pk.
IL24D31W240A	Cool White LED	240 VAC	Not provided	1
IL24D31W110A	Cool White LED	110 VAC	Standard US plug	1
IL24D31W024C	Cool White LED	24 V AC/ DC	Not provided	1
IL24D31W012D	Cool White LED	12 V DC	Not provided	1
IL24E31W240A	Warm White LED	240 VAC	Not provided	1
IL24E31W110A	Warm White LED	110 VAC	Standard US plug	1
IL24E31W024C	Warm White LED	24 V AC/ DC	Not provided	1
IL24E31W012D	Warm White LED	12 V DC	Not provided	1

<sup>\*\*</sup> Plugs available. Contact Altech.